



Wedgie
Part #48579

CAUTION: READ AND FOLLOW INSTRUCTIONS CAREFULLY BEFORE USE!

For asphalt shingles only, do not exceed 120 lbs, do not use during heavy rain or high winds. Do not stand or sit on this product as this may cause serious injury. Always examine this product before and after use, do not use if damaged. Do not throw this unit. Nail this unit to roof when not in use or if windy. This product like others should be used in compliance with Local, State, and Federal OSHA regulations.

General Directions:

Nail unit to roof when beginning starter row of shingles. After starter row has been completed, TranzSporter Wedgie may be positioned under shingle tabs and bundle placed on this unit. On roof pitches 8/12 and greater, the TranzSporter Wedgie must be nailed at all times; nail must go through roof truss. For asphalt shingles only, do not exceed 120 lbs, do not use during heavy rain or high winds. Do not stand or sit on this product as this may cause serious injury. Always examine this product before and after use, do not use if damaged. Do not throw this unit. Nail this unit to roof when not in use or if windy. This product like others should be used in compliance with Local, State, and Federal OSHA regulations.

Instruction Reference E1455

TIE DOWN ENGINEERING • 255 Villanova Drive SW • Atlanta, GA 30336
www.tiedown.com (404) 344-0000 Fax (404) 349-0401



E1455; 052016